



RUNWAY AND TAXIWAY MARKINGS

CHANGES: Mag var, dimensions of helipads, bearing strengths.

RWY No	DIRECTION MAG	THR	BEARING STRENGTH	AERODROME LIGHTING	PAPI	DECLARED DISTANCES					
						RWY	TORA M	TODA M	ASDA M	LDA M	
06	062°	59°15'19.87"N 024°10'55.23"E	RWY - PCN 120/F/A/W/T TWY A - PCN 120/R/C/W/T TWY B - PCN 104/F/A/W/T	PALS-I: RWY 06 900 M; LIH RWY 24 900 M; LIH	THR: RWY 06 G; LIH RWY 24 G; LIH	RWY 06 left 3°00'	06	2750	3050	2890***	2750
24	242°	59°15'49.33"N 024°13'39.03"E	TWY C - PCN 38/F/A/W/T TWY D - PCN 34/F/A/W/T TWY E* - PCN 39/F/A/W/T TWY F - PCN 120/R/C/W/T TWY H - PCN 120/R/D/W/T	REDL: RWY 06 2750 M, 60 M, W; last 600 M, Y; LIH RWY 24 2750 M, 60 M, W; last 600 M, Y; LIH	RENL: RWY 06 R; LIH RWY 24 R; LIH		RWY 24 right 3°00'	24	2750	2900	2890***
Helipad North		59°15'30.06"N 024°11'20.46"E	APN 1** - PCN 114/F/A/W/T APN 2** - PCN 37/F/A/W/T	RCLL: RWY 06 2750 M, 30 M, W; FM 2150 M - 2450 M, R/W; RWY 24 2750 M, 30 M, W; FM 2450 M, R; LIH FM 2150 M - 2450 M, R/W; FM 2450 M, R; LIH	TDZ: RWY 06 NIL RWY 24 NIL		Helipad	TODAH M	RTODAH M	LDAM M	
Helipad South		59°15'16.00"N 024°11'32.09"E	APN 3 - PCN 120/R/C/W/T APN 4 - PCN 120/R/B/W/T	STWL: RWY 06 150 M, R; RWY 24 150 M, R;	TWY: A, B, C, D, E, F, H; EDGE CL - NIL OBST: R; LIL		Helipad North	165	45	165	
Taxiways C, D, E		12 M wide.	Helipad North - NIL Helipad South - PCN 114/F/A/W/T				Helipad South	210	90	210	
Taxiways A, B, H		23 M wide.									
Taxiway F		22,5 M wide.									

LEGEND

- runway-holding position (Pattern A)
- runway-holding position (Pattern B)
- flood light

NOTES

- * TWY E PCN 0-1550 M 39/F/A/W/T 1550-1710 M 111/R/D/W/T
- ** APN 1 STANDS PCN 118/R/C/W/T APN 2 STANDS PCN 66/R/D/W/T
- *** MIL ASDA 2900 (SW Y (MIL) 150 x 45)